







MODEL	RANGE	SIZES	INPUT	HANDHELD EQUIPMENTS	REF.	
Handheld Temperature Equipments						
P-TER-MINI	-40/+150°C		included	Digital Handheld thermometer. For inside measuring. 0.1 °C Resolution. 1 Display of 3 1/2 digits. Plastic protection cover.	23001	
P-TER-PT	-200/+800°C		included	PT100 high precision thermometer. 2 Temperature measurings. Large display with 3 readings. 0.1 °C Resolution. Maximum and Minimum recording function. Alarms programming.	23002	
P-TER-K	-50/+1300°C	147x70 x39	K	Digital Handheld thermometer. For K probe. 1 Display of 3 1/2 digits. With decimal point. 0.1 °C Resolution. Anti-collision cover. Connectable to several probe types. Provided with 1 m. ambient probe (+10 +50 °C).	23003	
Options P-TER-K1 P-TER-K2	0/+600°C		K1 probe to puncture	K temperature probe. To puncture with handle. 3 M SILICONE cable. Stainless sheath (100x4ø to 6ø). With protection of Spring Cable .	2300A	
	0/+500°C		K1 probe SET	K temperature probe. With final perforated sheath and handle. 3 M SILICONE cable. Stainless sheath (100x4ø). With protection of Spring Cable . With final perforated sheath and handle.	2300B	
Handheld Infrared Temperature Equipments						
P-PIST	-50/+500°C	49x116 x208	infrared	Infrared gun with Laser pointer. Fixed emissivity of 0.95. Illuminated display. Automatic shut down. Provided with kit.	23004	
P-MAN	-20/+420°C	49x116 x208	infrared	Control of Infrared gun with Laser pointer. Recording function. Memory until 10 data. Programmable alarm. Illuminated display. Provided with kit.	23005	
Temperature and Humidity Handheld						
P-HR	0/+50°C 10%-95% RH	170x70 x30	Included	Handheld Thermo hydrometer with humidity indicator 10 to 95 Hr% and temperature. RS232 Communication Output. Probe with cable. 20 min Autostop	23006	
P-THR	-20.0/+60.0°C 1.0%-99.0% HR	225x50 x38	included	Handheld Thermo hydrometer with humidity indicator 1 to 99 HR% and temperature -20.0...+60.0 °C. Speed 2 measures/sec. Humidity Precision ±3%, Temperature Precision ±0.8°C.	23007	

HANDHELD

MODEL	RANGE	SIZES	INPUT	HANDHELD EQUIPMENTS	REF.	
Handheld Noise Measuring Equipments dBa.						
P-SON	30 db / 130 db		included	High Quality Sonometer Measurement type A and C. With Noise Suppressing System. For Relative Noises Measurement. Resolution 0.1 db. Precision +/- 1.5 %. Band Width 20 Hz a 12.5 KHz. Battery Supply.	23008	 P-SON
Handheld Air Speed Measuring Equipments						
P-AN	30db/130db		Included	Anemometer/Thermometer. From 0.4 m/s to 25 m/s air speeds. Temperature reading from - 10°C to +50°C. 2% accuracy. Memory key, Maximum and Minimum. RS-232 output.	23009	 P-AN
Handheld Rotations Measuring Equipments						
P-TAC	5Rpm/9999Rpm	215x65 x38	Included	Professional Digital Counter with double optical and contact function. Very useful for axels and bearings measurements. Up to 9999 RPM measuring. Optical from 5 RPM to 9999 RPM. Contact from 0.05 to 1999 RPM. Precision +/- 0.05 + 1 Digit. Measuring Selection in m/s or feet/s.	23010	 Ref. 9
Handheld Water PH Measuring Equipments						
P-PH	0 a 14 PH 0/+100°C 0/2000 mV	182x72 x32	Included	Professional PH measurer. Multifunction with may features for the exhaustive analysis in PH measuring. Ideal for laboratory and analysis process in substance manufacturing. Provided with protective case with PH4 and PH7 solutions for recalibration. PH measurements, Temperature, mV. Max. and Min Memory. Automatic temperature compensation.	23011	 P-PH
Handheld Water CO2 and Temperature Measuring Equipments						
P-CO2	0-10.000 y 0/+50°C	49x116 x208	Handheld	CO2 sensor + Handheld temperature. Dual LCD display . 80 hrs autonomy battery. Software calibration every 5 years. Analog 0-4V output.	23012	 P-CO2